CARBON DIOXIDE TRANSMITTERS CDT2000 DUCT SERIES

Multifunctional, duct mount CO₂ transmitters for building automation systems

The CDT2000 Duct series air quality transmitters are engineered for building automation systems in the HVAC/R industry. The CDT2000 Duct series measures carbon dioxide (CO_2) , utilizing the industry standard NDIR measurement principle, and temperature (T). Illuminated display ensures easy readability also from a distance. The CDT2000 Duct has a screwless lid and an easily adjustable mounting flange that make the installation of the device easy.

The CDT2000 Duct series transmitters calibrate themselves automatically using ABC^{TM} logic. The ABC^{TM} logic requires that the space in which the transmitter is used needs to to be unoccupied for four hours per day so that the indoor CO_2 concentration drops to the outside level. CDT2000-DC Duct is a dual channel model with a measuring channel and a reference channel that makes a continuous comparison and the necessary adjustment accordingly. CDT2000-DC Duct is also suitable for buildings that are continuously occupied.

CDT2000 Duct series devices include:

- Separate field configurable output for each measurement parameter (CO₂, T)
- Mounting flange

CDT2000 Duct series device options offer:

- Clear backlit display
- Modbus configuration

APPLICATIONS

CDT2000 Duct series devices are commonly used to monitor:

- CO₂ levels of incoming and return air in ventilation system
- CDT2000-DC Duct series devices can also be used in applications where there is a constant source of carbon dioxide present (for example hospitals and greenhouses)

MODEL SUMMARY

	CDT2000		
Description	Model	Product code	
Carbon dioxide transmitter, duct mounted	CDT2000 Duct	302.001.001	
- with display	CDT2000 Duct-D	302.001.002	
- with Modbus configuration and display	CDT-MOD-2000 Duct-D	302.001.006	
- with dual channel sensor	CDT2000-DC Duct	301.007.001	
- with dual channel sensor and display	CDT2000-DC Duct-D	301.007.002	
- with Modbus configuration, dual channel sensor and display	CDT-MOD-2000-DC Duct-D	301.007.003	



B



CARBON DIOXIDE TRANSMITTERS CDT2000 DUCT SERIES

SPECIFICATIONS

Performance

Measurement ranges: CO₂: 400-2000 ppm Temperature: 0...50 °C Accuracy: CO₂: ±40 ppm + 2 % of reading, DC model: 75 ppm or 10 % of reading (whichever is greater) Temperature: <0.5 °C

Technical Specifications

Media compatibility: Dry air or non-aggressive gases Measuring units: ppm and °C Measuring element: CO₂: Non-dispersive infrared (NDIR) Temperature: NTC10K Calibration: Automatic self-calibration ABC Logic[™] or continuous comparison (DC) Environment: Operating temperature: 0...50 °C Storage temperature: -20...70 °C Humidity: 0 to 95 % rH, non condensing

Physical

Dimensions: Case: 119 x 100 x 44.7 mm Probe: L=188 mm, d=12 mm Mounting: With flange, adjustable 0...188 mm Weight: 150 g Materials: Case: ABS Cover: PC Probe: ABS Protection standard: IP54 Electrical connections: 4 spring loaded terminals

4 spring loaded terminals (24 V, GND, CO₂, T) 0.2–1.5 mm² (12–24 AWG)

Electrical

Supply voltage: 24 VAC or VDC \pm 10 % Current consumption: max 230 mA (at 24 V) + 10 mA for each voltage output Output signals for every media: 0/2...5/10 VDC, Load R minimum 1 k Ω

Conformance

Meets requirements for CE marking: EMC Directive 2014/30/EU RoHS Directive 2011/65/EU WEEE Directive 2012/19/EU

COMPANY WITH MANAGEMENT SYSTEM CERTIFIED BY DNV GL = ISO 9001 = ISO 14001 =



HOW TO GENERATE A MODEL?

Example:	Product series								
CDT2000 Duct-D	CDT2000	Carbon dioxide transmitter, analog configurations							
	CDT-MOD-2000	Carbon dioxide transmitter, Modbus configuration							
		Calibration							
			ABC logic™, Automatic Background Calibration DC Dual channel, for continuously occupied space						
		-DC							
			Mounting						
				Wall mount					
			Duct	Duct mount (not available with relay or relative humidity sensor)					
			Relay (only for wall mount model)						
				-1R With relay					
				Without relay					
				Relative humidity			ty sensor (only for wall mount model)		
				-rH	-rH	With relative humidity sensor			
						Without relative humidity sensor			
						Display			
						-D	With display		
							Without display		
Model	CDT2000		Duct			-D			